

# 300M Wall Jack Fat Access Point

## W30AP(TH)



## Specification

Hardware Features	
Dimensions	86*86*35mm
Weight	104.6g(173.6g include the package)
AP Type	Fat AP
Interfaces	2*FE LAN ports 1*RJ11 Telephone port 1*USBv 2.0(Ipad not recommended)
Antennas	3dbi omni-directional antennas
Button	1*Reset
Power Method	802.3af PoE
Maximum Power Comsumption	9W
LED indicator	WiFi
Software Features	
Compliant Standards	IEEE 802.11n/g/b
Frequency Range	2.4GHz
Maximum wireless speed	300Mbps

Maximum Transmit Power	17 dBm*
Wireless Basic Settings	Multiple SSID Enable/Disable Wireless Radio Wireless Client isolation Wireless Access Control Wireless Client list SSID - to - VLAN Tagging
Wireless Security Settings	64/128 WEP WPA-PSK WPA2-PSK WPA & WPA2-PSK WPA WPA2
Working mode	AP
Maximum Concurrent Clients	12
LAN Settings	Static IP Dynamic IP
DHCP Server	DHCP Server Client list
VPN Pass - Through	PPTP L2TP
Management Tool	SNMP (v1& v2c) Reboot System Log Firmware update Time & Date Setting Backup/Restore Configuration Username Management Diagnostic Tool(ping)
<b>Other</b>	
Package Contents	300 Wall Jack Fat Access Point W30AP Quick Installation Guide Ethernet cable Two Screws Resource CD
Operating Temperature	-10°C ~ 45°C
Storage Temperature	-30°C ~ 70°C
Operating Humidity	10% ~ 90% non-condensing
Storage Humidity	10% ~ 90% non-condensing
Default Settings	IP Adress: 192.168.0.254 Login Username: admin Login Username: admin
Certifications	FCC/CE/Rohs

\*For Thailand country