



IP-COM WLAN Solution For Enterprises

——Up to 50 people



1. Requirements
2. Solutions
3. Benefits
4. Recommendations

1. Requirements of office scenarios




Enterprise with up to 50 people

1. Requirements Summary

1 Separated internal and external networks




2 Good wireless network experience



3 Easy and fast deployment




4 Easy maintenance



1. Requirements
2. Solutions
3. Benefits
4. Recommendations

2. Solutions——General Design





Enterprise with up to 50 people

2. Solutions——Key Locations Network Deployment

Low voltage silo

SG-PRO-9P: Small size, can be placed in a Low voltage silo; support up to 4 ISP access, can power up to 8 terminals devices; greatly reduce the cost of enterprise networking.




Palm size



2. Solutions——Key Locations Network Deployment

Reception: Ceiling-mounted AP for coverage of relatively open area

The reception area is relatively open and requires Wi-Fi coverage with smooth roaming without dead zone; working network and guest network need to be set up separately. Ceiling-mounted AP can provide large area coverage and support fast roaming and VLAN mapping



Separated Guest and Staff SSID

Guest

Staff

Different roles

Guest SSID

Staff SSID

Access rights

Only to external
networks. 2Mbps
speed limit


Independent
access for staff.
3Mbps speed limit

Access authentication

2. Solutions——Key Locations Network Deployment

Office zone deployment: Multiple ceiling-mounted APs for coverage of large area

Good Wi-Fi coverage and fast roaming is required for connected devices moving in large office zone; Based on the size of office zone and the number of connected devices, using ceiling APs to ensure high-speed and stable network with good WiFi coverage and smooth roaming.



Ceiling AP

Wide Coverage

Designed with high gain omni-directional antennas , per AP to cover up to 500m².

Smooth Roaming

Support 802.11k/v protocol fast roaming, roaming switching time is less than 50ms.



High Speed

Wi-Fi 6 standard with maximum rates of up to 3000Mbps per AP.

2. Solutions——Key Locations Network Deployment

Meeting Room: In-wall AP for performance and aesthetics

Meeting rooms are small in size and have a small number of connected devices. Each room is covered by one in-wall AP; It is aesthetically pleasing with high speed and stable wireless access.



In-wall AP

Elegant
appearance

Stylish design with a wide range of colours to suit all decoration styles.

Easy installation


Supports PoE power supply and only requires one Ethernet cable.

High speed

3000Mbps wireless rate

2. Solutions——Network topology

Enterprise with up to 50 people




1. Requirements
2. Solutions
3. Benefits
4. Recommendations

3. Benefits

Benefit 1: One-click for internal and external network isolation


Guest Network SSID can easily distinguish accesses for guests and staff; Company staff can connect to office network via a password and guests need to connect to Guest Network SSID




3. Benefits

Benefit 2: High quality wireless network experience


Seamless roaming



Load balancing



Automatic channel optimisation



- Channel 1
- Channel 6
- Channel 11

3. Benefits

Benefit 3: Easy installation and fast configuration



Quick set-up wizard, no engineering experience required

Installation: A quick setup wizard automatically pops up when you connect to WiFi, so you can complete your network setting in two easy steps.

Maintenance: APP & Cloud platform ensure real-time project status monitoring, aftersales maintenance and remote operation.

SSID	Property	Operation
IPCOM Pro-6-LR	Cloud Configuration	Unbind

Select Device
1 devices selected

SSID-1
Keep unchanged
☒ All RFs ☒ 2.4GHz ☒ 5GHz

SSID-2
Keep unchanged
☒ All RFs ☒ 2.4GHz ☒ 5GHz

SSID-3
Keep unchanged
☒ All RFs ☒ 2.4GHz ☒ 5GHz

SSID-4
Keep unchanged
☒ All RFs ☒ 2.4GHz ☒ 5GHz

SSID-5
Keep unchanged
☒ 2.4GHz

Auto Optimization

Auto Optimization
The system will automatically collect and analyze the usage of wireless resources, and adjust the configuration such as the channel and power of wireless devices.
Last optimization: No optimization records in the current network [Start Optimization](#)

Scheduled Optimization Settings
Scheduled optimization is disabled now. [Scheduled Optimization](#)

Optimization Records
No optimization records
records in total [Details](#)

Manual Optimization

Enter keywords to search

Model	Status	Remarks	Management Mode	IP Address	MAC Address	2.4 GHz RF	5GHz RF
Pro-6-LR	Online	Pro-6-LR	Cloud Management	192.168.1.100	C8:3A:35:26:81:A8	13/29dBm	56/29dBm

Total 1 items < 1 > 5 items/page


3. Benefits

Benefit 4: Integrated Router, AC Controller and PoE Power Supply, easy to install and manage



Full-featured and Cost-saving

Router, AC and 8-port PoE switch all-in-one, eliminating the need for an AC and PoE-powered switch, resulting in a much lower total solution cost.





3. Benefits

Benefit 5: Easy to use, effortless project experience



Only need a phone

- Automatic pre-sales solution generation and online consultation;
- Gateway, switch, AP managed by APP
- APP One-Click Network configuration
- ;
- Engineering acceptance tests, e.g. signal, network speed;
- Automatic report generation



Rapid negotiation, no struggle for solutions



Rapid deployment, simple operation and maintenance






Rapid acceptance, no delays in project delivery

1. Requirements
2. Solutions
3. Benefits
4. Recommendations





4. Recommendations

——Cost-effective Wi-Fi5 solution

Scene	Device	Model	Image	Features	Layer
Server room/ Low voltage silo	Gateway	SG-PRO-9P		<ul style="list-style-type: none">• 9*Gigabit Ethernet ports, 8*PoE ports• Max PoE power supply of single port: 30W• Max PoE power supply of whole device: 95W	Core layer
Meeting room	In-wall AP	W36AP		<ul style="list-style-type: none">• 300Mbps+867Mbps• 2*Gigabit Ethernet ports• 18dBm+16dBm	Access layer
Office zone	Ceiling AP	W63AP		<ul style="list-style-type: none">• 300Mbps+867Mbps• 1*Gigabit Ethernet Port• 26dBm+26dBm	Access layer

4. Recommendations

——High Performance Wi-Fi6 Solution

Scene	Device	Model	Image	Features	Layer
Server room/ Low voltage silo	Gateway	SG-PRO-9P		<ul style="list-style-type: none">• 9*Gigabit Ethernet ports, 8*PoE ports• Max PoE power supply of single port: 30W• Max PoE power supply of whole device: 95W	Core layer
Meeting room	In-wall AP	Pro-6-IW		<ul style="list-style-type: none">• 574Mbps+2402Mbps• 2*Gigabit Ethernet ports• 20dBm+20dBm	Access layer
Office zone	Ceiling AP	Pro-6-LITE		<ul style="list-style-type: none">• 574Mbps+2402Mbps• 1*Gigabit Ethernet Port• 26dBm+26dBm	Access layer
Reception/Office zone	Ceiling AP	Pro-6-LR		<ul style="list-style-type: none">• 574Mbps+2402Mbps• 2*Gigabit Ethernet ports• 29dBm+29dBm	Access layer

IP-COM / THANKS

WORLD WIDE WIRELESS